

WHAT IS CLAIMED IS:

1. A method for applying electrical energy to a patient's outer skin comprising:

5 positioning an active electrode adjacent to or near a target site on a patient's outer skin; and

applying sufficient high frequency voltage to the active electrode to remove the stratum corneum without removing the entire epidermis layer.

10 2. The method of claim 1 further comprising removing a layer of skin having a thickness less than about 30 microns.

15 3. The method of claim 1 further comprising stimulating the growth of new collagen in the patient's skin underlying the removed stratum corneum.

4. The method of claim 3 wherein the stimulating step is carried out by removing the dead skin cells from the patient's outer skin and accelerating the growth of new skin cells.

20 5. The method of claim 3 wherein the stimulating step is carried out by applying thermal energy to the underlying dermis and epidermis.

25 6. The method of claim 1 further comprising applying a high frequency voltage difference between the active electrode and a return electrode in the presence of an electrically conductive fluid, wherein the conductive fluid generates a conductive path between the active and return electrodes.

30 7. The method of claim 1 further comprising maintaining a space between the active electrode and the patient's outer skin during the applying step.

8. The method of claim 7 wherein the space is at least about 0.5 mm.

9. The method of claim 7 wherein the space is at least about 1.0 mm.

10. The method of claim 6 further comprising applying a sufficient high frequency voltage difference between the active and return electrodes to vaporize a portion of the electrically conductive fluid, and to ionize the vaporized fluid into a plasma adjacent to the active electrode.

5

11. The method of claim 6 further comprising delivering the electrically conductive fluid to the target site during the applying step.

12. The method of claim 11 further comprising cooling the electrically
10 conductive fluid.

13. A method for applying electrical energy to a patient's outer skin comprising:

15 positioning an active electrode adjacent to or near a target site on a patient's outer skin having a first outer layer and a second layer underlying the first outer layer; and applying sufficient high frequency voltage to the active electrode to remove the first outer layer while maintaining a temperature at the exposed surface of the second layer less than about 50°C.

20 14. The method of claim 13 wherein the temperature at the exposed surface of the second layer is less than about 40°C.

25 15. The method of claim 13 wherein the first layer has a thickness in the range of about 5 to 30 microns.

16. The method of claim 13 wherein the first layer is the stratum corneum and the second layer is the epidermis.

30 17. The method of claim 13 further comprising stimulating the growth of new collagen in the patient's skin underlying the first outer layer.

18. The method of claim 13 further comprising applying a high frequency voltage difference between the active electrode and a return electrode in the

presence of an electrically conductive fluid, wherein the conductive fluid generates a conductive path between the active and return electrodes.

19. The method of claim 13 further comprising maintaining a space
5 between the active electrode and the first outer layer during the applying step.

20. The method of claim 19 wherein the space is at least about 1.0 mm.

21. The method of claim 18 further comprising applying a sufficient high
10 frequency voltage difference between the active and return electrodes to vaporize a portion of the electrically conductive fluid, and to ionize the vaporized fluid into a plasma adjacent to the active electrode.

22. The method of claim 18 further comprising delivering the electrically
15 conductive fluid to the target site during the applying step.

23. The method of claim 22 further comprising cooling the electrically conductive fluid prior to the delivering step.

20 24. An apparatus for applying electrical energy to a patient's outer skin comprising:

an electrosurgical instrument having a shaft with proximal and distal ends
and an electrode assembly at the distal end of the shaft, the electrode assembly comprising
an active electrode spaced from a return electrode; and

25 a power supply coupled to the electrode assembly for applying a sufficient high frequency voltage difference between the active and return electrodes to remove the stratum corneum of the patient's outer skin without removing the entire epidermis layer.

25 25. The apparatus of claim 24 further comprising an electrically
30 insulating support member between the active and return electrodes.

26. The apparatus of claim 25 wherein the electrically insulating support member comprises a material selected from ceramic, glass and silicone.

112
out basis
27. The apparatus of claim 24 wherein the active electrode comprises a loop electrode extending from the electrically insulating support member.

5 28. The apparatus of claim 24 further comprising a fluid delivery element for delivering electrically conductive fluid between the active and return electrodes.

10 29. The apparatus of claim 24 further comprising an insulating offset coupled to the distal end of the shaft and extending distal to the active electrode to space the active electrode from tissue in contact with the offset.

15 30. The apparatus of claim 24 further comprising an insulating shield coupled to the distal end of the shaft, the shield having a distal surface spaced distally from the active electrode, such that when the distal surface of the shield is adjacent to, or in contact with, tissue at a target site, the shield forms a chamber between the active electrode and the tissue.

20 31. The system of claim 24 wherein the return electrode is positioned on the instrument and spaced proximally from the active electrode.

32. The system of claim 24 wherein the return electrode is positioned within the chamber and spaced from the active electrode.

25 33. The system of claim 24 comprising a single active electrode terminal.

30 34. The system of claim 24 comprising a plurality of electrically independent active electrode terminals.

35. The system of claim 24 comprising a plurality of non-electrically independent active electrode terminals.

36. The system of claim 28 wherein the active and return electrodes are configured, upon the application of a sufficient high frequency voltage in the presence of electrically conductive fluid, to generate a plasma within the chamber.

5 37. The system of claim 36 wherein the plasma is generated at a location spaced a distance of about 0.05 to 1.5 mm from the tissue, wherein the active and return electrodes are configured, upon the application of a sufficient high frequency voltage in the presence of electrically conductive fluid, to accelerate ions from the plasma in the chamber such that the ions contact the tissue, the ions having sufficient energy to ablate the
10 contacted tissue.

38. The system of claim 28 further comprising an aspiration lumen having distal opening coupled to the chamber for aspirating fluid from the chamber.

15 39. An apparatus for applying electrical energy to a patient's outer skin comprising

an electrosurgical instrument having a shaft with proximal and distal ends and an electrode assembly at the distal end of the shaft, the electrode assembly comprising an active electrode spaced from a return electrode;

20 a power supply coupled to the electrode assembly for applying a sufficient high frequency voltage difference between the active and return electrodes to remove the stratum corneum of the patient's outer skin; and

wherein the electrode assembly is configured to remove the stratum corneum while maintaining a temperature at the target site below about 50°C.

25